

## Technical data

# Farm Manager



ENERGY STORAGE  
E3DC

ENERGY STORAGE  
E3DC

A member of Hager Group

# Technical data

## Farm Manager

### Input

Input connection technology	1x Ethernet 1x cable gland (network connection) 6x double membrane seal 1x CAN (connection in housing)
AC connection voltage (V)	230
AC power consumption (A)	0.08
AC rated frequency (Hz)	50

### General data

Permissible ambient temperature (°C)	+5 to +35
Max. relative humidity (non-condensing) (%)	85
Max. operating altitude (mamsl)	2000
Protection rating	IP20
Dimensions WxHxD (mm)	296x370x160
Weight (kg)	6.14
Warranty	Statutory

### Protection measures

AC short-circuit-proof	Yes
Protection class	I

### Equipment

Approvals	CE DIN EN 61000-6-2 2019-11 DIN EN 61000-6-3 2022-06 DIN EN 62368-1
Energy management	Integrated
Display	7" TFT display
Data interface	Ethernet
Communication protocols	TCP/SCP
Supported home automations	–

The terms and conditions of HagerEnergy GmbH apply. Internet connection required for remote maintenance and checking the yield.



HagerEnergy GmbH  
Ursula-Flick-Straße 8  
D-49076 Osnabrück

P +49 541 760 268 0



e3dc.com



+ Wallbox  
+ Inverter  
+ HEMS

Your E3/DC partner